

Internal Screens

Assembly Guide







Heritage Internal Screens


Introduction

Intended for internal use only, the system has no drainage and requires little assembly on site.

Hinged doors will be provided with a screwed in temporary wooden threshold (to keep secure in transit) which needs removal on site.

All fixing screws shall be suitable for the structure and the application. Please refer to relevant parts of BS 8213-4 for installation guidance.

All products should be fitted plum, level and square.



Duration Windows reserve the right to make changes to the product specifications as technical developments dictate, and without prior notice. Pictures shown are for illustrative purposes and are not binding in detail, colour or specification.

Deglazing (Reverse to Glaze)

Deglazing



GLAZED UNIT



REMOVE WEDGE GASKET



PUSH BEAD IN & ROTATE OUT



REMOVE GLASS

Example here is for a fixed internal screen. All products will follow the same general procedure.

Duration Windows reserve the right to make changes to the product specifications as technical developments dictate, and without prior notice. Pictures shown are for illustrative purposes and are not binding in detail, colour or specification.

3


E.& O.E.

Coupling

Coupling Products



TEST FIT



DEGLAZE



DRILL & COUNTERSINK



FIX SCREWS

When coupling it is advised to deglaze all products or consult the technical manual to see available space in glazing cavity.

Duration Windows reserve the right to make changes to the product specifications as technical developments dictate, and without prior notice. Pictures shown are for illustrative purposes and are not binding in detail, colour or specification.

Toe & Heeling Process

Toe & Heeling

This is intended only as a guide.


All doors are unique and may require different packing levels.


If you are unsure please contact a professional.

Windows and doorsets in most cases are delivered temporally glazed for ease of delivery and to insure all parts arrive safely. We advise that all glass is removed and re-packed to suit site installation.

Plastic Glazing Packers

Images shows the recommended positions of the plastic packers recommended in BS-6262.







Duration Windows reserve the right to make changes to the product specifications as technical developments dictate, and without prior notice. Pictures shown are for illustrative purposes and are not binding in detail, colour or specification.

Main Office & Factory

Thames Development, Charfleets Road, Canvey Island, Essex. SS8 0PQ 01268 681612 (20 lines) sales@duration.co.uk www.duration.co.uk

Product Showroom

Unit 1 Casino Parade, Eastern Esplanade, Canvey Island, Essex. SS8 7FJ 01268 695100

SatNav Directions Use: SS8 7DN.